



Blue Heat/Net Sync

Connect Tech's Blue Heat/Net Sync offers an Ethernet-to-serial solution for synchronous/asynchronous data communications.

Based on the robust μ CLinux (Linux embedded operating system) the Blue Heat/Net Sync can be programmed with application specific protocols. Blue Heat/Net Sync incorporates multiple electrical interfaces, and remote configurability to free devices from a physical connection. Remote access increases location flexibility and simplifies future installations or upgrades, reducing costs.

The Blue Heat/Net Sync can be configured and controlled via serial interface or remotely. With the option to boot from on-board flash memory or a network location, updating devices in the field can be done from a central location.

Product Name: Blue Heat/Net Sync
Part Number: BMG006



Asynchronous models available



Specifications	
Number of Ports	4
Serial Line Interfaces	Software switchable; V.28 (RS-232), V.10 (RS-423), V.11 (RS-422, X21), V.35, EIA-530, EIA-530A, V.36 (RS-449) - Termination resistors for V.11 and V.35
Encoding Modes	NRZI: NRZ, NRZB, NRZI-Mark, NRZI-Space Bi-Phase: Bi-Phase-Space, Bi-Phase-Manchester, Differential Bi-Phase
Control Signals	Single ended: TxD, RxD, DTR, DSR, RTS, CTS, RI, DCD, RxClock, TxClock Differential: TxD+/-, RxD+/-, RTS+/-, CTS+/-, DTR+/-, DCD+/-, DSR+/-, RxClock, TxClock
Baud Rate	Synchronous: up to 10 Mbps Asynchronous: up to 230.4 Kbps
Synchronous Protocols	DLC, HDLC, MonoSync, BiSync, Transparent BiSync (with 16 and 32 bit CRC checking)
LAN Interface	10Base-T, 100Base-TX Ethernet (auto-sensing)
Platform	66MHz CPU with 16 MB SDRAM and 8 MB Flash
Configuration	Web configuration or via serial port
Dimensions	Length: 133 cm/5.24" Width: 244 cm/9.61" Height: 43 cm/1.69"
Temperature	Operating Temperature: 0°C to 60°C (32°F to 140°F)
Clocking	Software selectable internal/external clocking. External clocking is provided on TXC and RXC pins
Bipolar Clock	Clock input accepts sin or square wave signals up to 10 Mbps, +/- 10 V
ESD Protection	15 kV
Power Requirements	5 V DC (2.4A) to 30 V DC (450mA) using DC barrel or Phoenix screw terminal connector. Optional DC power supply
Rack Mount	1U, 19" rack mountable
Regulatory Approvals	EN 55022, EN 55024, FCC/ICES-003
Warranty and Support	Lifetime warranty and free technical support

FEATURES

- ✓ Four synchronous/asynchronous Ethernet-to-serial ports
- ✓ Synchronous protocols: V.28, V.10, V.11, V.35, EIA-530 and V.36
- ✓ Software selectable internal and external clocking modes
- ✓ Web configurable or via serial port
- ✓ Auto-sensing, 10Base-T, 100Base-TX Ethernet LAN interface
- ✓ μ CLinux operating system
- ✓ Speeds up to 10 Mbps
- ✓ DB-25 serial connectors
- ✓ 1U, 19" rack mountable

Specifications subject to change without notice.

©2011, Connect Tech Inc. All trademarks are property of their respective holder.

RoHS

Connect Tech Inc.
42 Arrow Road, Guelph ON Canada
Tel: 519.836.1291 **Fax:** 519.836.4878
Toll: 800.426.8979 (North America)
Email: sales@connecttech.com
www.connecttech.com