



FieldTab7

Connect Tech's FieldTab7 is a rugged built tablet for use in the most extreme environmental conditions. It's hyper dimming technology, provides a wide brightness adjustable display, ideal for day and night operations. The FieldTab7 has a wide range of accessories available to adapt it to your particular application as needed.

With one gigabit Ethernet port, two USB ports, one digital I/O port, one COM port and two CAN buses, the FieldTab7 is well suited to a wide range of applications.




Hand Strap




Handle




Vehicle Dock



Desktop Dock



MSR +
Barcode Reader



External Battery



Battery Charger



Shoulder Strap



Car Adapter



Stylus

FEATURES

- ✓ IP65, MIL-STD-810G, 5 feet drop resistance
- ✓ Sunlight readable function
- ✓ Seamless communication, optional 3.5G
- ✓ Up to 9 hours of battery life
- ✓ 2MP and 5MP cameras with auto focus and LED flash
- ✓ Optional MSR and barcode reader 2-in-1 module
- ✓ Wide coverage accessories
- ✓ Compact vehicle dock with wide range voltage power

Specifications

CPU	Intel® Dual Core Atom N2600 1.6GHz (Cedar Trail)
Memory	2GB DDRIII
Storage	32GB half-slim SATA SSD
Display	7-inch 1280 x 800 WXGA, 400nits / optional 700nits sunlight readable, 5-wire resistive touch
RF	Wi-Fi 802.11 a/b/g/n, Bluetooth v4.0, 3.5G (option), GNSS (GPS/QZSS/GLONASS)
Data Collection	2MP front camera, 5MP rear camera w/ auto focus and LED flash, 1D/2D barcode reader + MSR 2-in-1 snap-on module (option)
Security	TPM 1.2
Power Adapter	AC 100V~240V, 50~60Hz input; 19VDC @3.42A, 65W
Battery	Internal battery, 2900mAh, 7.4V External battery, 4200mAh, 7.4V (hot-swappable, option)
I/O Interface	• USB 2.0 type A x 1, • Micro USB x 1, Micro SD x 1, Micro SIM x 1, • Ethernet (RJ-45) x 1, RS-232 x 1, • Audio jack (Microphone/Headphone combo) x 1, speaker x 1, • 32-pin docking connector x 1
Dimensions and Weight	22.5 x 16.8 x 2.7 cm (8.9" x 6.6" x 1"), 2.09 lbs (0.95kg)
Operating System (options)	Windows Embedded Standard 7 32-bit Windows 7 Professional 32-bit
Environment	Operating Temp -20°C to 50°C, Storage Temp -30°C to +70°C Humidity 5% ~ 95%
In-box Accessories	Stylus, Hand Strap, Shoulder Strap, Handle, Adapter

RoHS

Specifications subject to change without notice.
©2014, Connect Tech Inc. All trademarks are property of their respective holder.

Connect Tech Inc.
42 Arrow Road, Guelph ON Canada
Tel: 519.836.1291 **Fax:** 519.836.4878
Toll: 800.426.8979 (North America)
Email: sales@connecttech.com
www.connecttech.com